



Product Data & Specification Sheet

Ultravex Panels

1. Product Overview

GretaGrove Ultravex Panels are large format decorative wall panels for modern trade interiors, combining an ultra slim 3 mm profile with a durable, scratch resistant decorative surface. At 2400 mm x 1220 mm, each panel covers a full wall height in a single sheet with minimal joints, delivering a seamless, premium result at speed. Fully waterproof and mould resistant, Ultravex is suited to bathrooms, shower enclosures, kitchens, feature walls, showrooms, and commercial spaces, providing a practical, cost effective alternative to tiles and plaster. Panels are supplied with a matching range of trims and accessories for a complete finished system.

2. Key Features

- 100% waterproof and moisture resistant, ideal for wet and humid environments including shower enclosures
- Mould and mildew resistant for long lasting performance and a hygienic surface
- Scratch resistant surface designed for everyday durability and extended use
- Ultra slim 3 mm profile for installations where space is limited or a thinner panel is preferred
- Large 2400 mm x 1220 mm format covers full wall heights with minimal joints
- Lightweight design for easy handling, reducing installation time and labour costs
- Easy to cut and fit without the need for specialist tools
- Low maintenance, simple to clean with just a damp cloth
- Available in a range of decors to suit any interior scheme

3. Technical Specification

Material	Rigid PVC composite sheet with UV cured decorative face
Panel Length	2440 mm
Panel Width	1220 mm
Panel Thickness	3 mm
Coverage per Panel	2.93 m ²
Weight	6.3 kg per m ²
Panels per Carton	1
Edge Profile	Square edge, joined with matching trims or sealed butt joints
Fire Classification	-
Water Resistance	Fully waterproof, suitable for wet rooms and shower areas when installed

Operating Temperature	-10°C to plus 50°C
Thermal Movement	Allow an expansion gap at all perimeter edges and fixtures as stated in the Installation Guide
Decor Availability	Nine decors including Clyde Gloss, Carrara Marble, Carrara Gold, Burnt Gloss, Black Marble, White Gloss, River Stone, Grey Marble, and Graphite Marble. Refer to the current GretaGrove range listing.
Surface	Decorative scratch resistant face, wipe clean, no further decoration required

4. Composition and Manufacture

Ultravex Panels are manufactured as a rigid composite sheet with a decorative face applied and cured during manufacture for surface hardness and scratch resistance. The panel requires no further treatment, painting, or sealing of the face. The material is fully recyclable at end of life through appropriate rigid plastic recycling streams.

5. Applications

Suitable for internal walls in bathrooms, shower enclosures, en suites, kitchens, splashback areas, utility rooms, WCs, feature walls, hallways, offices, showrooms, retail units, salons, catering environments, and other domestic and commercial interiors. Not suitable for external use, floors or worktops, or areas of sustained high temperature such as directly behind hobs without suitable clearance or a protective barrier. Panels are decorative cladding and are not a structural or load bearing product; heavy items must be fixed through to the substrate behind.

6. Installation

Bond direct to a suitable, sound, flat, dry substrate using an adhesive such as Froggit Adhesives, with joints, edges, and junctions finished using matching trims and sealant. Allow panels to acclimatise for a minimum of 24 hours before fitting and maintain an expansion gap at all perimeter edges. In wet areas, all edges, joints, and junctions with sanitaryware must be sealed with sanitary grade silicone.

7. Handling, Storage, and Packaging

Panels are supplied by the carton. Store cartons flat, indoors, fully supported across their full area, away from heat sources and direct sunlight, and protected from moisture. Given the large format and slim profile, carry panels on edge with two people, supporting the panel across its width, and do not flex panels excessively or drag panels across each other. Check batch numbers where multiple cartons are used within the same installation.

8. Warranty and Supporting Documents

This product is covered by the GretaGrove 10 year product warranty, subject to its terms and conditions. This sheet should be read alongside the GretaGrove Ultravex Panels Installation Guide, Product Warranty, and Fire Rating Certificate, all available from GretaGrove on request.

9. Important Information

The information in this sheet is provided in good faith and is correct at the date of issue. Values stated are typical and may be subject to normal manufacturing tolerances. Minor variations in colour, pattern, and surface between production batches are a normal characteristic of the product. GretaGrove reserves the right to amend the specification without notice as part of continuous product development. It is the responsibility of the specifier and installer to confirm the suitability of the product for the intended application.

Bargain Depot LTD t/a GretaGrove | 107-109 St Barnabas Road, Leicester, LE5 4BW | 0116 298 2545 |
orders@gretagrove.co.uk | gretagrove.co.uk